



VIRGINIATILE

A Division of Artivo Surfaces™

COLLECTION	JASPER	DIAMOND	TETON	YOSEMITE
CORE CONSTRUCTION	RIGID CORE (SPC)	RIGID CORE (SPC)	RIGID CORE (SPC)	RIGID CORE (SPC)
STONE CONTENT	70% +	70% +	70% +	70% +
TOTAL THICKNESS	5mm	6.5mm	5mm	5mm
WEAR LAYER	20mil	28mil	20mil	20mil
WIDTH	9"	9"	9"	7.5"
LENGTH	73"	60"	60"	48"
ATTACHED PAD	1mm IXPE anti-microbial	1mm IXPE anti-microbial	1mm XPO	1mm XPO
SURFACE TEXTURE	EIR (Embossed in Register)	EIR (Embossed in Register)	High Definition	High Definition
BEVEL TYPE	Painted	Micro-Bevel	Micro-Bevel	Micro-Bevel
TOP COATING	Commercial ceramic bead	Commercial ceramic bead	Scratch Shield™ MAX Coating	Scratch Shield™ MAX Coating
GLOSS LEVEL	Matte	Matte	Matte	Matte
LOCKING SYSTEM	UniClic Angle Lock	UniClic Angle Lock	I4F Drop Lock	I4F Drop Lock
PATTERN REPEAT	8 Unique Faces *	8 Unique Faces *	20 unique Faces *	24 Unique Faces *
FLOOR SCORE CERTIFIED	Yes	Yes	Yes	Yes
RADIANT HEAT COMPATIBLE	Yes ** Hydronic	Yes ** Hydronic	Yes ** Hydronic	Yes ** Hydronic
WARRANTY				
RESIDENTIAL	Lifetime	Lifetime	Lifetime	Lifetime
LIGHT COMMERCIAL	15 Years	20 Years	15 Years	15 Years
FULL COMMERCIAL	5 Years	10 Years	5 Years	5 Years