



## Eco Ultimate Silencer



Roll size: 36" x 33.34' (100SF)  
Roll weight: 16 lbs  
Thickness: 1.9mm (.075")  
Polyurethane foam with reground tire fill  
Foam Density: 25 lbs/ft<sup>3</sup>  
Installation Method: Glue Down/  
Float/ Nail  
Floor Type: Laminate/ Engineered  
Hardwood/ Hardwood/ Bamboo  
Includes moisture barrier  
IIC: 73  
STC: 73  
IIC 22  
Compression Set 8.3%

### What's so great about this product:

- Polyurethane foam has great compression set resistance (lower number the longer it lasts in the application)
- Rolls out flat for easy installation
- Highly sustainable as we use Castor based polyols instead of Petroleum based polyols, and 100% post consumer ground tire
- Made in USA
- This is a premium, long lasting, high performance product

## Eclipse II:



Roll size: 43" x 27.9' (100SF)  
Roll weight: 5.5 lbs  
Thickness: 1.8mm (.070")  
EVA foam  
Foam Density: 11.7 lbs/ft<sup>3</sup>  
Installation Method: Float only  
Floor Type: Floating Laminates/  
Engineered Hardwood/  
Solid Rigid Core Vinyl  
Includes moisture barrier  
IIC: 72  
STC: 66  
IIC 25  
Compression Set 16.3%

### What's so great about this product:

- EVA foam is usually lower density, this density is high for EVA in flooring
- Resists mold and mildew because the foam is closed cell and does not absorb moisture
- Very high IIC and STC ratings
- This is a cost-effective choice for cost sensitive installations