


COLLECTION	LAKESHORE	SEASIDE
CORE CONSTRUCTION	HDF (High Density Fiberboard)	HDF (High Density Fiberboard)
TOTAL THICKNESS	12mm	12mm
WEAR LAYER COATING	AC4 Melamine (commercial grade)	AC4 Melamine (commercial grade)
WIDTH	7.5"	9.25"
LENGTH	48"	72"
ATTACHED PAD	NO *	NO *
SURFACE TEXTURE	EIR (Embossed in Register)	EIR (Embossed in Register)
BEVEL TYPE	Painted	Painted
RUN LENGTH	65' Without transitions	65' Without transitions
GLOSS LEVEL	Matte	Matte
LOCKING SYSTEM	Angle Snap Uniclic	Angle Snap Uniclic
PATTERN REPEAT	24 Unique Faces	10 Unique Faces
FLOOR SCORE CERTIFIED	Yes	Yes
RADIANT HEAT COMPATIBLE	Yes ** see installation guidelines	Yes ** see installation guidelines
GRADE	ON, ABOVE, or BELOW	ON, ABOVE, or BELOW
SUBFLOOR	Wood / Concrete	Wood / Concrete
TEMPERATURE TOLERANCES	60 ⁰ -85 ⁰ F	60 ⁰ -85 ⁰ F
RELATIVE HUMIDITY TOLERANCES	30-65 % RH	30-65 % RH
WARRANTY		



RESIDENTIAL	Lifetime	Lifetime
LIGHT to MEDIUM COMMERCIAL	10 Years	10 Years
PVC FREE	YES	YES
COUNTRY OF ORIGIN	VIETNAM	VIETNAM
TRANSITONS	T, QR, REDUCER, END CAP, SN	T, QR, REDUCER, END CAP, SN
STAIR TREADS	N/A	N/A