



TECHNICAL INFORMATION



V3 Moderate Variation



Stock



Recommend offset pattern $\leq 33\%$



DCOF: ≥ 0.65




Frost Resistant




Water Absorption: $< 0.5\%$




COLORS




White
VTC KSWH



Ivory
VTC KSIV



Gray
VTC KSGY



Taupe
VTC KSTP

Performance Characteristics

Breaking Strength	> 350 lbf
Chemical Resistance	Class A
DCOF	≥ 0.65
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	8
Water Absorption	$< 0.5\%$
Certifications	N/A
Country of Origin	
Shade Variation Code	V3

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
20" x 20"	19.69" x 19.69"	8.50mm	Matte/Natural
12" x 24"	11.81" x 23.62"	8.40mm	Matte/Natural
12" x 24" Textured	11.81" x 23.62"	8.40mm	Matte/Natural
13" x 13"	12.99" x 12.99"	7.60mm	Matte/Natural
2" x 2" Mosaic	11.77" x 11.77"	8.40mm	Matte/Natural

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

