Stowe

Virginia Tile Company

Porcelain

VIRGINIATILE

TECHNICAL INFORMATION

V3 Moderate Variation

Ready Ship

DCOF: ≥ 0.60

Frost Resistant

Water Absorption: ≤ 0.5%

Made in USA

COLORS



Beige
VTC SOBE



Gray
VTC SOGR



Brown
VTC SOBR

Performance Characteristics

Breaking Strength	≥ 425 lbs
Chemical Resistance	Class A
DCOF	≥ 0.60
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	7
Water Absorption	≤ 0.5%
Certifications	Greenguard
Country of Origin	USA
Shade Variation Code	V3

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
24″ x 48″ Rectified	23.56″ x 47.31″	9.00mm	Polished
24″ x 48″ Textured Rectified	23.56″ x 47.31″	9.00mm	Bush-hammered/ R11
24″ x 24″ Rectified	23.56″ x 23.56″	9.00mm	Polished
24″ x 24″ Textured Rectified	23.56″ x 23.56″	9.00mm	Bush-hammered/ R11
12″ x 24″ Rectified	11.75″ x 23.56″	9.00mm	Polished
12″ x 24″ Textured Rectified	11.75″ x 23.56″	9.00mm	Bush-hammered/ R11
3″ x 3″ Hexagon Mosaic Textured Rectified	10.25″ x 11.75″	9.00mm	Bush-hammered/ R11
4″ x 12″ Bullnose Rectified	4.00″ x 11.75″	9.00mm	Polished
4″ x 12″ Bullnose Textured Rectified	4.00″ x 11.75″	9.00mm	Bush-hammered/ R11

* Not all sizes are available in all colors and finishes.

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

** These recommendations are not defined by ANSI Standards

Please see virginiatile.com for details